

Model 660SJC

TELESCOPIC BOOM LIFTS



GREATER PLATFORM CAPACITY

- Newly designed with 10% more unrestricted platform capacity than previous model. Dual platform capacity available.

MORE PRODUCTIVE

- Equipped with track drive for easier manoeuvrability on muddy terrain.
- Reaches full height quicker for increased productivity on the job site.

MORE ACCESS

- Large work envelope including an articulating jib for a wider range of motion.

MORE COMFORT

- Increased operator comfort due to end of cylinder stroke dampening.

Standard Features

- 0.91 m x 1.83 m low mount platform
- Side entry with drop bar mid rail
- Multiple function operation
- Full proportional drive joystick control with integral thumb steer switch
- Full proportional main boom and swing joystick control
- Multiple speed control for telescope and platform rotate
- Selectable creep speed on drive / lift and swing functions
- 1.83 m articulating jib
- 180 degree powered platform rotator
- Platform console machine status light panel ¹
- Load sensing system
- AC cable to platform
- Engine distress warning/shut down system ²
- Gull-wing hoods
- 5 degree tilt alarm and indicator light
- Steel tracks
- Lifting/tie down lugs
- Hour meter
- Ground control selector switch with key lock
- Platform tool tray
- 12V DC auxiliary power
- Hydraulic oil cooler
- Cast Aluminum Control Box
- Horn
- Hydrostatic drive transmission
- Swing-out engine tray
- Control ADE® Advanced Design Electronics System
- JLG Skyguard active system

¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

Standard Specifications

Power Source	
• Diesel Engine - Deutz TD 2.9 L4	50kW
• Fuel Tank Capacity	117 L
Hydraulic System	
• Hydraulic System	129 L
• Auxiliary Power	12V DC

³ Available when integrated with the SkyPower® package.

⁴ Includes all-motion alarm and flashing amber beacon.

⁵ Includes platform mounted work lights and head & tail lights.

⁶ Includes console cover, boom wipers and cylinder bellows.

⁷ Available only with drop bar mid rail.

Accessories & Options

- 0.91 m x 2.44 m low mount platform
- 0.76 m x 0.89 m low mount platform ⁷
- Side entry with drop bar mid rail
- Side entry with inward swing gate
- 13 mm air line to platform
- Rubber Track Pads
- On-board 4,000 W generator
- SkyPower® package 7,500 watt on-board generator
- SkyWelder® package 250 amp welder in the platform ³
- All motion alarm
- Alarm package ⁴
- Light package ⁵
- Head and tail lights
- Platform flood lights
- Chassis illumination lights
- Flashing amber beacon
- Euro Plug & Socket
- Hostile environment kit ⁶
- Skyguard beacon
- Generator hourmeter
- Synthetic Biodegradable Hydraulic Oil
- Biodegradable Hydraulic Oil
- Fire Resistant Hydraulic Oil
- Platform worklights
- Special paint colour



Model 660SJC

TELESCOPIC BOOM LIFTS

Performance


Working Height	21.99 m
Working Outreach	18.04 m
Swing (continuous)	360°
Platform Capacity – Unrestricted	2 / 250 kg
Platform Capacity – Restricted	3 / 340 kg
Platform Rotator (hydraulic)	180°
Jib – Overall Length	1.83 m
Jib – Range of articulation	130° (+70°/-60°)
A. Platform Size	0.91 m x 1.83 m
B. Overall Width	2.49 m
C. Tailswing (working condition)	1.22 m
D. Stowed Height	2.50 m
E. Stowed Length	10.79 m
F. Wheelbase	2.76 m
G. Ground Clearance	0.42 m
Machine weight ¹	13,308 kg
Maximum Ground Bearing Pressure	TBC
Drive Speed	2.57 km/h
Gradeability	55%
Turning Radius	Zero
Type of Tracks ²	Steel
Track Width	0.50 m

¹ Certain options or country standards may increase weight and/or dimensions.


² Optional detachable rubber pads available



Reach Diagram



Dimensions



IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



Tel: 0333 335 5140

enquiries@skyreachaccess.com

www.skyreachaccess.com